

DULUX White Ceiling Paint

PRODUCT CODE 615-32276

Data Sheet No. AUDD0024

APPROVALS GPC-L-26/4, APAS-0260/5, AS3730, Part 1.

Description

DULUX White Ceiling Paint is an interior flat white water based paint with outstanding hiding power for use on ceilings.

Features

Water based
Outstanding opacity
Flat finish

Benefits

Same day recoat, easy clean up and low odour
Usually covers with one coat - saves application time
Hides plastering imperfections - ideal for low ceilings

Uses

DULUX White Ceiling Paint is specifically designed to minimise the labour in painting ceilings and provide a flat finish. One coat carefully applied by roller will give a satisfactory appearance in most cases.

Performance Guide

Weather Not suitable for exterior application.

Heat Up to 60C

Solvent Poor solvent resistance.

Acid NA

Salt NA

Water For interior use in dry areas. Not recommended for damp areas.

Abrasion Not applicable.

Alkali NA

Typical Properties and Application Data

Gloss Level 0-3 at 60 degrees

Gloss Level Ind
Volume Solids 28.0

Colour White

V.O.C Level < 30g/L untinted

Touch Dry 20 Minutes

Clean Up Clean all equipment with water.

Thinner Water

Spread Rate 12.2 sqm/L

Components 1.0

Toxicity Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.

Wet film per coat Recommended 82 µm

Dry film per coat Recommended 23 µm

Recoat 2 Hours

Application Method


Data Sheet	DULUX White Ceiling Paint		
DuSpec Data Code	AUDD0024	Page No	1 of 3
Issue No	6.0	Date Issued	08/07/2008

DULUX White Ceiling Paint

Data Sheet No.	AUDD0024
-----------------------	-----------------

Application Guide

Surface Preparation

All surfaces must be thoroughly cleaned and free of all loose dirt, dust, grease, loose or flaking paint, and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth. For Plasterglass in Western Australia first apply one coat of DULUX Plaster Ceiler.

Application Procedure and Equipment

Stir contents thoroughly before and during use with a broad flat stirrer using an upward lifting action.

Brush/Roller: Apply full even coats direct from container. If necessary, thin with up to 100 ml water per litre to assist application.

Airless/Conventional Spray: Suitable for application by all standard spray equipment. Up to 125 ml water per litre may be added to aid atomisation.

Brush, roller, conventional and airless spray.

Health and Safety

MSDS Number 36586

Health Effects For detailed information refer to the product label and the current Material Safety Data Sheet available through Customer Service.
Health Effects: Splashes to the eye may cause eye irritation. When spraying, inhalation of mists may produce respiratory irritation..

Protective Equipment Personal Protective Equipment: Wear eye protection and when spraying wear a dust mask

In the case of emergency please call 1800 033 111

Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings. Do not exceed recommended spreading rate. Avoid exposure to steam and condensation for 48 hours after application. Although the film is dry to touch in 20 minutes, allow 7 days for the film to fully cure before lightly cleaning with a sponge wet with detergent solution. Do not paint at temperatures below 10 degrees Celsius or when the temperature of surface may fall below 10 degrees Celsius during the drying period.

Transport and Storage

Pack A 615-32276

Sizes 4 Litre 10 Litre

Weight 6.0 Kg 14.8 Kg

Dangerous Goods Class NA

Shipment Name Not dangerous goods.; No special transport requirements.

Flash point NA

UN Number NA

Package Group NA

Data Sheet	DULUX White Ceiling Paint		
DuSpec Data Code	AUDD0024	Page No	2 of 3
Issue No	6.0	Date Issued	08/07/2008



DATA SHEET



DULUX White Ceiling Paint

Data Sheet No. AUDD0024

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of Orica Consumer Products in relation to goods manufactured by it or their use and application is given in good faith and is believed by Orica Consumer Products to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Orica Consumer Products is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon Orica Consumer Products by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of Orica Australia Pty Ltd ABN 99 004 117 828. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

Orica Consumer Products 1970 Princes Highway Clayton, Victoria 3168 AU ABN 99 004 117 828

Data Sheet	DULUX White Ceiling Paint		
DuSpec Data Code	AUDD0024	Page No	3 of 3
Issue No	6.0	Date Issued	08/07/2008