

**INTERGRAIN Ultradeck**

PRODUCT CODE 552-Line

Data Sheet No. AUDW1285

APPROVALS

**Description**

Intergrain Ultradeck is an exceptionally durable, long lasting water based oil for decking, garden furniture and all other timber.

**Features**

Water based.  
Lightly pigmented.  
Weather resistant.

**Benefits**

Fast dry and easy clean up.  
Enhances the look of timber.  
Good durability and resistance to U.V.


**Uses**

Suitable for exterior decking, garden furniture, railings and walkways.

**Performance Guide**

<b>Weather</b>	Formulated for exterior use.	<b>Salt</b>	Good.
<b>Heat</b>	Up to 70C. Higher temperatures will cause film to soften.	<b>Water</b>	Good water resistance.
<b>Solvent</b>	Sensitive to aromatic solvents and alcohols.	<b>Abrasion</b>	Moderate abrasion resistance.
<b>Acid</b>	Fair.	<b>Alkali</b>	Fair.

**Typical Properties and Application Data**

<b>Gloss Level</b>	Low sheen	<b>Thinner</b>	Do not thin.
<b>Gloss Level Ind</b>		<b>Spread Rate</b>	12.0 sqm/L
<b>Volume Solids</b>	21.0	<b>Components</b>	1.0
<b>Colour</b>	Natural	<b>Toxicity</b>	Dry film is non-toxic.
<b>V.O.C Level</b>	< 30g/L	<b>Wet film per coat</b>	Recommended 83 µm
<b>Touch Dry</b>	1 hour	<b>Dry film per coat</b>	Recommended 18 µm
		<b>Recoat</b>	4 hours

Application Method



# INTERGRAIN Ultradeck

<b>Data Sheet No.</b>	<b>AUDW1285</b>
-----------------------	-----------------

## Application Guide

### Surface Preparation

Wash all uncoated new or old timber with Intergrain Reviva Timber Cleaner, closely following label instructions. Ensure surface is rinsed clean and allowed to dry thoroughly.

Previously painted timber or timber coated with a product that seals the surface must have the coating removed back to bare timber. A combination of paint remover and power washing, or sanding is recommended.

Previously oiled or stained timber where the coating does not seal the timber, wash with Intergrain Reviva Timber Cleaner, closely following label instructions. Ensure surface is rinsed clean and allowed to dry thoroughly.

### Application Procedure And Equipment

Stir thoroughly before and during use.

Apply two coats of Intergrain Ultradeck using a quality synthetic or pure bristle brush, pad applicator or spray (HVLP or airless). If spraying, backbrush after each section is coated to ensure a uniform finish. Apply along the length of the board including exposed edges and end grain. If necessary, sand lightly between coats to remove any raised grain.

If using Ultradeck in conjunction with UltraGrip, DO NOT sand between coats.

### Notes

#### SPREADING RATES

For Softwood: 10-12 m<sup>2</sup>/L

For Hardwood: 12-14 m<sup>2</sup>/L

#### SLIP RESISTANCE RATING

When Intergrain UltraGrip is added to Intergrain Ultradeck at the recommended addition rate, the resultant Ultradeck coating achieves the following slip rating:

Tested to AS/NZS 4586-2004 Slip resistance classification of new pedestrian surface materials - Appendix D : OIL - WET Ramp

Slip Resistance Assessment Group : R12

## Health and Safety

**MSDS Number** 21104

**Health Effects** Splashes to eyes will cause irritation. Prolonged skin contact with liquid is harmful and inhalation of vapour or spray mists may produce respiratory irritation and headaches.

**Flammability** This product is non-flammable.

**Protective Equipment** Wear eye protection, protective clothing and gloves. If spraying wear a respirator with a combined vapour/particulate cartridge.

**Disposal** Do not dispose down the drain. Refer to your local council for correct disposal procedures.

**In the case of emergency please call 1800 033 111**

## Precautions and Limitations

Do not apply if temperature is below 10C or likely to fall below that during the drying period. Do not apply to hot surfaces or those in direct sunlight, on hot windy days, or in temperatures above 30C. Do not apply if rain or dew is likely within 4 hours of application.

<b>Data Sheet</b>	INTERGRAIN Ultradeck		
<b>DuSpec Data Code</b>	AUDW1285	<b>Page No</b>	2 of 3
<b>Issue No</b>	7.0	<b>Date Issued</b>	08/07/2008

**INTERGRAIN Ultradeck**

<b>Data Sheet No.</b>	<b>AUDW1285</b>
-----------------------	-----------------

**Transport and Storage**

<b>Pack A</b>	552-Line					
<b>Sizes</b>	1L	4L	10L	<b>Weight</b>	1Kg	4.5Kg 11.1Kg
<b>UN Number</b>	NA			<b>Dangerous Goods Class</b>	NA	
<b>Package Group</b>	NA					

**Disclaimer**

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the DuSpec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of Orica Consumer Products in relation to goods manufactured by it or their use and application is given in good faith and is believed by Orica Consumer Products to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Orica Consumer Products is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon Orica Consumer Products by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the DuSpec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of Orica Australia Pty Ltd ABN 99 004 117 828. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

Orica Consumer Products 1970 Princes Highway Clayton, Victoria 3168 AU ABN 99 004 117 828

<b>Data Sheet</b>	INTERGRAIN Ultradeck		
<b>DuSpec Data Code</b>	AUDW1285	<b>Page No</b>	3 of 3
<b>Issue No</b>	7.0	<b>Date Issued</b>	08/07/2008