

DULUX Matt Clear Coat

PRODUCT CODE 690-84893

Data Sheet No. AUDD0064

APPROVALS NA

Description

DULUX Matt Clear Coat is a low gloss, waterbased, clear finish that provides added protection in high traffic and wet areas over DULUX Suede Effects. (NOTE: cannot be used over Glimmer, Metallic or Pearlustre effects).

Features

Waterborne paint
Stain resistance
Impervious clear coating
100% acrylic paint

Benefits

Water wash up, low odour
Improved washability
Improved resistance to wear and tear
Suitable for use in wet areas

Uses


DULUX Matt Clear Coat is suitable for interior use over low sheen or flat paint systems, such as DULUX Suede effects, that require added protection against moisture and wear and tear.

Performance Guide

Weather Recommended for interior use. Exterior durability unknown.
Water Suitable for use in wet areas after 24 hrs dry time
Abrasion Good mar and polish resistance

Heat Resists temperatures up to 60C.
Solvent Sensitive to hydrocarbons and alcohols

Typical Properties and Application Data

| | | | |
|------------------------|---|--------------------------|-------------------------|
| Gloss Level | Low gloss | Thinner | Water (not recommended) |
| Gloss Level Ind |  | Spread Rate | 14.0sqm/L |
| Volume Solids | 26.0 | Components | 1.0 |
| Toxicity | Lead free. Dry film is non toxic and conforms to AS1647, Part 3. | Number of Coats | 1 |
| V.O.C Level | < 35g/L | Wet film per coat | Recommended 69 µm |
| Touch Dry | 30 mins | Dry film per coat | Recommended 18 µm |
| Clean Up | Clean all equipment with water | Recoat | 3 Hours |

Application Method


DULUX Matt Clear Coat

| | |
|-----------------------|-----------------|
| Data Sheet No. | AUDD0064 |
|-----------------------|-----------------|

Application Guide

Surface Preparation

DULUX Matt Clear Coat can be applied over DULUX Suede effects or any other previously painted flat or low sheen surfaces that are in good condition. Allow surface to dry thoroughly before applying Matt Clear Coat.

Application Procedure and Equipment

Stir well using a broad, flat paddle with an up and down scooping action. Apply one even coat of DULUX Matt Clear Coat.

Brush/Roller: Use a medium nap roller (10-12mm pile). Pre-wet brushes and rollers with water before commencing application. Thinning is not recommended.
Brush or roller

Health and Safety

MSDS Number 45509

Health Effects For detailed information refer to the product label and the current Material Safety Data Sheet available through Customer Service on 13 25 25 Health Effects: Splashes to the eye may cause eye irritation.

Protective Equipment Personal Protective Equipment: Wear eye protection.

In the case of emergency please call 1800 033 111

Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings. The temperature must be between 10C and 30C during application, and remain above 10C during drying. Under cool or humid conditions, allow longer times to dry.

Transport and Storage

Pack A 690-84893

Sizes 1 Litre

Weight 1.0 Kg

Dangerous Goods Class NA

Shipment Name Not dangerous goods.; No special transport requirements.

Flash point NA

UN Number NA

Package Group NA

| | | | |
|-------------------------|-----------------------|--------------------|------------|
| Data Sheet | DULUX Matt Clear Coat | | |
| DuSpec Data Code | AUDD0064 | Page No | 2 of 3 |
| Issue No | 4.0 | Date Issued | 11/08/2008 |



DATA SHEET



| | |
|------------------------------|--------------------------------|
| DULUX Matt Clear Coat | |
| | Data Sheet No. AUDD0064 |

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of Orica Consumer Products in relation to goods manufactured by it or their use and application is given in good faith and is believed by Orica Consumer Products to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Orica Consumer Products is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon Orica Consumer Products by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of Orica Australia Pty Ltd ABN 99 004 117 828. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

Orica Consumer Products 1970 Princes Highway Clayton, Victoria 3168 AU ABN 99 004 117 828

| | | | |
|-------------------------|-----------------------|--------------------|------------|
| Data Sheet | DULUX Matt Clear Coat | | |
| DuSpec Data Code | AUDD0064 | Page No | 3 of 3 |
| Issue No | 4.0 | Date Issued | 11/08/2008 |